



EXCELAM- Q1100RS Q1670RS

Dual core adaptor for
77mm and 58mm film core



Prographics Hot & Cold Roll Laminators

- Easy to use for outer rewriter tension control
- Applied dual film core and stronger unwinder shaft
- Enhanced clutch function and easy to use for outer pressure tension knob
- Hot and cold lamination
- Speed and temperature control
- Automatic power shut-off and stand-by system
- Top and bottom independent temperature control
- Back Trimmer for limited web removal

LARGE FORMAT GRAPHIC
ROLL LAMINATORS

EXCELAM-Q series

www.gmp.com

Large Format Graphic Roll Laminator

EXCELAM-Q1100RS/Q1670RS are the perfect machines for wide range of service in a copy shop environment or in a copy center, graphic printing shop and photo shop. Ideal for laminating posters, inkjet prints, leaflets, maps wide photographs with superb results, and for truly professional mounting up to 13mm-thick GMP LAMIBOARD® (Foam board)

Superb laminating results on a wide range of standard laminating films from 25mic to 500mic, including PHOTONEX soft touch film and SUPERTOUCH hard touch film.

Features include variable speed, temperature and pressure control, as well as LCD panel, pre-set function, mounting facility, pouch lamination and cold film setting.

Features

- Tension control on film mandrel
- Laminating speed up to 3m/min
- Paper guide on feed table
- Max. 13mm thickness for foamboard mounting
- Variable pressure control
- No special power supply needed only requires standard household power outlet



Specifications

Model Name	EXCELAM-Q1100RS	EXCELAM-Q1670RS
Max. Laminating Speed	3m/min	3m/min
Max. Laminating Width	1100mm	1670mm
Laminating Films	25mic~500mic	25mic~500mic
Substrate Thickness	80g/m ² ~350g/m ²	80g/m ² ~350g/m ²
Thickness Mount	13mm	13mm
Front Roller Diameter	80mm	80mm
Rear Roller Diameter	60mm	60mm
Power Requirements	220~240V, 50/60Hz	220~240V, 50/60Hz
Power Consumption	3300W, 15A	3300W, 15A
Warm up Time	22 minutes	25 minutes
Heating System	Hot Roller Internal Infrared Heater	Hot Roller Internal Infrared Heater
Operating Temperature	150°C Max.	150°C Max.
Speed Control	Key Pad	Key Pad
Temperature Control	Key Pad	Key Pad
Pressure Adjustment	Manual (7step)	Manual (7step)
Film Core	77mm/Dual	77mm/Dual
Cooling System	Blower	Blower
Dimensions(WxLxH)	1500 x 710 x 1250mm	2000 x 710 x 1250mm
Type of Main Motor	DC W-Geared Motor /36V80	DC W-Geared Motor /36V80
Type of Rewinder Motor	Link to Main Motor	Link to Main Motor

※ GMP reserves the right to change specifications without prior notice.