



SURELAM PRO- 380D 500D

- Single side laminator and encapsulator
- Laminating speed 7m/min
- Manual feeding and cutting, decurling bar



- Maximum laminating speed of 7m/min
- Increased film capacity
- Turbo cooling system
- Feeding guide on feed table
- Safety shield
- Pre-set functions 8-bit micro-processor controlled
- LCD display helps to eliminate operator error
- Decurling device for single side lamination
- Heat shoe & hot roller combination
- Top and bottom film alignment system (Patented)

TRADE ROLL
LAMINATORS

SURELAM PRO series

www.gmp.com

Trade Roll Laminator

For encapsulating processing shop and printing shop.

This heat shoe & hot roller type roll laminator is designed for office, photo copy shop or commercial laminating service center.

With variable speed control up to 7 meters per minute and variable temperature control.

The SURELAM PRO series which has combination of heat shoes & hot roller system can handle all industry standard films up to 500microns

Features

- Include 8-bit microprocessor control with pre-set functions and lcd readout
- Pressure control
- Unique film tracking system for easy film alignment
- Cross cutter and turbo power cooling system
- Side lays on feed table
- Opening heat shoes for easy roller cleaning and larger roll film capacity



Specifications

Model Name	SURELAMPRO-380D	SURELAMPRO-500D
Max. Laminating Speed	7m/min	7m/min
Max. Laminating Width	380mm	500mm
Laminating Films	25mic~500mic	25mic~500mic
Substrate Thickness	80g/m ² ~ 350g/m ²	80g/m ² ~ 350g/m ²
Front Roller Diameter	50mm	50mm
Rear Roller Diameter	50mm	50mm
Power Requirements	220~240V, 50/60Hz	220~240V, 50/60Hz
Power Consumption	3000W, 12.6A	3000W, 12.6A
Warm up Time	7 minutes	7 minutes
Heating System	Heat Shoe & Infrared Heater	Heat Shoe & Infrared Heater
Operating Temperature	150°C Max.	150°C Max.
Speed Control	Key Pad	Key Pad
Temperature Control	Key Pad	Key Pad
Pressure Adjustment	Manual (5step)	Manual (5step)
Film Core	19-58WH	19-58WH
Cooling System	Blower	Blower
Dimensions(WxLxH)	610 x 615 x 460mm	760 x 615 x 460mm
Type of Main Motor	DC W-Geared Motor	DC W-Geared Motor

※ GMP reserves the right to change specifications without prior notice.